



HANDHELD PNEUMATICS

TEX light and medium
breaker range

Atlas Copco

TAKING CARE OF TALENT

When you are in demand, it's important to use your energy in the right way. By picking the right tool, you'll be a breaker – not a shaker.

Our light and medium range breakers can handle most tasks. And just like you, they're unique. The Solid body design means the whole breaker is made from one single casting. Thanks to the technology, we can skip the bolts that are often used to keep the machine together. In fact, our breakers have between 25 and

35 less parts than other breakers. Fewer parts make simple servicing and better reliability. For you that translate to a little more done every day and a lot of time saved each month. To keep yourself in shape we recommend you use HAPS-enabled machines. With far less vibration

levels you can work up to six times longer per day. Less vibration is important for productivity, especially if you are multitasked. All vibration work adds up during the day. With HAPS you can take on tasks without having to worry about reaching excessive vibration levels. That's taking care of talent.

TEX Pneumatic light breakers		140 PS		180 PS		220 PS			150 PE		190 PE	
Vibro-reduced		NO		NO		NO			YES		YES	
Weight	kg	15.5		19	19.5	22	23.5	23.5	19		22.5	23
Length	mm	590		595	645	625	670	670	590		595	645
Air consumption at 6 bar	l/s	25		26		30			25		26	
Impact rate	blows/min	1,530		1,500		1,320			1,530		1,500	
Vibration level 3 axes (ISO 28927-10)	m/s²	15.2		14.5		12.8			4.5		3.7	
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	104		104		104	106	106	104		104	
Sound pressure level (ISO 11203)	Lp, r=1m	91		92	91	92	93	93	91		92	91
Shank size: Hex	mm	22x82.5	25x108	25x108	28x160	25x108	28x160	32x160	22x82.5	25x108	25x108	28x160
Part number		8461 0223 30	8461 0223 32	8461 0224 30	8461 0224 34	8461 0225 30	8461 0225 32	8461 0225 35	8461 0223 31	8461 0223 33	8461 0224 31	8461 0224 33

Important: Full details of measurement are available in the Safety and Operating Instruction of the product (part no 9800 0683 90). They can be found on www.acprintshop.com

TEX Pneumatic light breakers		20 PS	20 PS-1	21 PE	21 PE-1
Weight	kg	20	20	21	21
Length	mm	635	600	650	615
Air consumption at 6 bar	l/s	25	25	25	25
Impact rate	blows/min	1,140	1,140	1,140	1,140
Vibration level 3 axes (ISO 28927-10)	m/s ²	18.3	18.3	7.6	7.6
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	105	105	105	105
Sound pressure level (ISO 11203)	Lp, r=1m	93	93	93	93
Shank size: Hex	mm	25x108	-	25x108	-
Part number		8461 0223 31	-	8461 0225 31	-
Shank size: Round	mm	-	25x75	-	25x75
Part number		-	8461 0224 33	-	8461 0226 33

Important: Full details of measurement are available in the Safety and Operating Instruction of the product (part no 9800 0683 90). They can be found on www.acprintshop.com

Accessories	Part number
Hand hose 20 mm x 3 m complete with claw coupling, wing nut and hose clamps	9030 2048 00
Claw coupling, Atlas Copco Standard	9000 0306 00
Claw coupling, Atlas Copco Standard with strainer	9000 0306 01

Please note: the above hand hose is equipped with Atlas Copco standard claw couplings.