



Outlet socket centres U 32B/U 63B



** We now give a five-year guarantee on purchases of new products. Simply visit our website to register and enter your product details.*

Outlet socket centres U 32B/U 63B

The new U 32B and U 63B outlet socket centres are designed to provide space for multiple circuit breakers and earth fault breakers. This allows a number of earth fault breakers to be fitted for each outlet socket. For example, 30 mA per 32A outlet socket.

It is easy to check or replace circuit breakers or earth fault breakers without removing the insert.

The hinges and doors have been strengthened.

The U 63B can easily be fitted (over and above the standard outlet sockets) with 3 additional CEE 216 outlet sockets.

Product benefits:

- Plenty of module positions.
- Strong hinge construction.
- Reinforced door.
- Easy to take out inserts.
- Easy to replace circuit breakers and earth fault breakers without having to remove the whole insert.
- The U 63 B can be fitted with 3 CEE 216 outlet sockets in addition to standard fitting.



Technical Data, U 32B/U 63B

	U 32B	U 63B
Rated current:	32A	63A
Voltage:	400V	400V
Coating class:	IP44	IP44
Labelling:	CE, S och FI	CE, S och FI
Dimensions:	Height 710 mm, width 540 mm, depth 250 mm (Unfolded frame 350 mm).	Height 930 mm, width 780 mm, depth 280 mm (Unfolded frame 520 mm).
Weight:	21 kg	30 kg
Standard fittings:	6xschuko 3xCEE 416 1xCEE 432 4xEarth fault breakers 30mA	6xschuko 3xCEE 416 1xCEE 432 4xEarth fault breakers 30mA 1xEarth fault breaker 300mA

El-Björn AB
Tel: +46 371-588 100
Fax: +46 371-181 34
E-post: info@elbjorn.se
www.elbjorn.se

091016-CB